



nush

## **KEY FEATURES**

- Signature model Gives you access to the superior ROLLSROLLER production method
- Low cost fast set up easy to handle GREAT VALUE
- ROLLSROLLER quality
- Ergonomic traverse ROLLSROLLER
- Lots of space for storage
- Optimized media holder on bed end.



info@rollsroller.se rollsroller.se +46 54 770 70 10

**ROLLSROLLER** SIGNATURE is our newest member that gives you access to the ROLLSROLLER production method.

It comes flat packed for access to any sign shop environment.

With a low investment cost, quick installation and easy operation, it gives you all the conditions to produce quality products and profitable sign making for many years. The optimized media holder on the bed end allows the operator to facilitate all four sides of the table and also for storage of vinyl etc.

## **ROLLSROLLER**<sup>®</sup> SIGNATURE 420/1705

| MODEL NAME                                    | ROLLSROLLER 420/170S         |
|---|------------------------------|
| Part No.                                      | 122-007                      |
| Model type                                    | Signature                    |
| Flatbed Length                                | 4240 mm / 13 ft. 10,9 in.    |
| Flatbed Width                                 | 1700 mm / 5 ft. 6,9 in.      |
| Length of working area                        | 3940 mm / 12 ft. 11,1 in.    |
| Width of working area (Roller width)          | 1630 mm / 5 ft. 4,2 in.      |
| Work height Flatbed                           | 875 mm / 2 ft. 10,4 in.      |
| Overall width incl. mounted Glide Beam        | 1970 mm / 6 ft. 5,6 in.      |
| Overall height incl. mounted Glide Beam       | 1335 mm / 4 ft. 4,6 in.      |
| Weight Flatbed Applicator                     |                              |
| Flatbed surface                               | Tempered glass + Cutting Mat |
| Electrical Voltage                            | 110-250VAC, 50-60Hz          |
| Required air supply                           | 6-8 bar / 87-116 psi         |
| Set pressure during operation                 | 3-5 bar / 43,5-72,5 psi      |
| Packing weight (Flatbed Applicator + package) |                              |
| Package Flatbed Applicator (LxWxH)            |                              |
| Wheels  | Yes (4)                      |
| Warranty                                      | 5 year limited warranty *    |
| User Manual                                   | ENG                          |
|   |                              |

\* Visit rollsroller.com/our-products/warranty/ for more information